

# UltraLine

SX-UL-1000-O-DGWW1a



## Outdoor Fixed Led Display



# Technical data LED Screen: UltraLine

Product Details	SX-UL-1000-O-DGWv1a	
Pixel Pitch (mm)	10,00	
Physical Density (Pixel/m2)	10.00	
LED Type	SMD 3535 Gold Wire	
Pixelcard Size (mm)	300 x 300	
Pixelcard Resolution (Pixel)	30 x 30	
Drive Mode	Constant Current Drive / Common Cathode	
Horizontal Viewing Angle (Deg.)	140	
Vertical Viewing Angle (Deg.)	120	
Brightness NIT (cd/m2)	7.000	10.000 (With Option)
Grey Scale	12-16 Bit	
Refresh Rate (Hz)	≤ 3.840	
High Refresh Rate IC Driver	High Refresh	
Max Power Consumption (W/m2)	~ 600	~ 600
Average Power Consumption (W/m2)	~ 240	~ 280
Cabinet Size (mm)	600mm / 900mm / 1200mm (H/V)	
Cabinet Resolution (Pixel)	60 / 90 / 120	
Cabinet Thickness (mm)	~ 90	
Weight (kg/m2)	~27 kg / sqm plus wiring	
Cabinet Material	Aluminum	
Serviceability	Front- & Rear Service	
Input Voltage (V)	AC 240V +/- 10% @ 50Hz	
Protection Level	IP 65	
Working Temperature (°C)	-20° – +60°	
Operation Humidity (RH)	10% - 85%	
LED Control System Design	Novastar	
Certificates	CE, ROHS, PFC, EMC Class A, LVD	
Options	High Brightness, Energy Saving	

We reserve the right to alter technical details without prior notice. 05/2024 ToKi

